



1330SE

Micro Scissor Lift

- 13 ft. (3.9 m) Platform Height Indoors and 19 ft. (5.9 m) Working Height Indoors
- Fits on Most Elevators with Shortest Overall Length and Low GVW (Gross Vehicle Weight)
- 24 in. (61 cm) Roll-Out Deck Extension with Incremental Lock Positions
- Direct Electric Drive for Exceptional Duty Cycle, Smooth Control and Fewer Leak Points
- 2-Person Platform (Indoors)/ 1-Person Platform (Outdoors) with 500 lb. (227 kg) Capacity
- Fully Proportional Lift and Drive Controls
- Ultra Compact Design Fits Into Small and Tight Work Areas
- Compact Size Yet Still Provides a Generous Work Area

Lightweight, Micro Slim Scissor with True Slide-Out Deck



Standard Features

Work Area

Roll-Out Deck Extension with Incremental Locking Positions
 Standard Swing Gate
 Lanyard Attachments
 110v Power to Platform

Performance

Direct Electric Drive
 Fully Proportional Drive and Lift Controls
 Up to 25% Gradeability

Power

24v DC, 85Ah AGM Battery Pack (Maintenance-Free)
 Battery Charge Indicator
 Single 110v Receptacle at Chassis for Common Plug Connection for Battery
 Charger and Power to Platform

Serviceability

Lubrication-Free Scissor Bearings
 Easy Maintenance Access to Mechanical and Electrical Components
 Logically Grouped Components and Numbered Wiring for Easy Reference

Safety

Lift Control Orientation Designed to Mitigate Overhead Entrapment	Descent Alarm
Dedicated Compartments Protect Electrical and Hydraulic Components	Drive Speed Interlock
Emergency Shut-Off at Platform and Lower Controls	Scissor Maintenance Lock
Non-Skid Metal Deck Construction	Multi-Axis Tilt Sensor
	Multiple Disc Brakes
	Automatic Parking Brake

Other Features

Removable Upper Controls	Non-Marking Tires
Voltage-Compensating Fully Automatic Battery Charger	All Motion Alarm
Hour Meter	Fork Lift Pockets
Machine Tie Downs	Flashing Beacon (Continuous)

Optional Features

900W Inverter	Proactive Platform Safety System® (PPSS)
Tool Tray	Leak Containment System® (LCS)
Pipe Rack	- Patent #11,112,060
Cold Weather Package	Second Year Extended Warranty
Anti-Fatigue Mat	



MEC Aerial Work Platforms

Tel: 559.842.1500 | 1401 S. Madera Avenue, Kerman, CA 93630 | USA
 Toll free: 1.877.MEC LIFT | 1.877.632.5438 | Fax: 559.842.1520
 Email: info@MECawp.com | www.MECawp.com

MEC®, Proactive Platform Safety System® and Leak Containment System® are registered trademarks of California Manufacturing & Engineering Co., LLC.
 Leak Containment System® is Patent #11,112,060

97010 DTD 1122

1330SE	U.S.	Metric
Heights		
Indoor Working Height*	19 ft.*	5.9m*
Outdoor Working Height*	16 ft.*	5 m*
Indoor Platform Height	13 ft.	3.9 m
Outdoor Platform Height	10 ft.	3 m
Stowed Height (Top Guardrail)	80 in.	203 cm
Stowed Height (Platform Floor)	35 in.	89 cm
Guardrail Height	39 in.	99 cm
Toeboard Height	6 in.	15 cm
Ground Clearance (Stowed)	2.5 in.	6 cm
Ground Clearance (Elevated)	0.6 in.	1.5 cm
Dimensions		
Length-Stowed (Overall)	57 in.	145 cm
Length-Stowed (Ladder Removed)	51 in.	130 cm
Chassis Width	31.5 in.	80 cm
Platform Length (Extended)	75 in.	191 cm
Platform Length (Retracted)	51 in.	130 cm
Roll-Out Deck Length	24 in.	61 cm
Platform Width	27.5 in.	70 cm
Wheelbase	41 in.	104 cm
Total Lift Capacity	500 lbs.	227 kg
Personnel Capacity	2 (Indoors); 1 (Outdoors)	
Roll-Out Deck Capacity	250 lbs.	113 kg
Speed		
Raise/Lower Speed	20 s	20 s
Drive Speed (Stowed)	2.5 mph	4.0 km/h
Drive Speed (Elevated)	0.5 mph	0.8 km/h
Performance		
Gradeability	25%	25%
Turning Radius (inside)	18 in.	46 cm
Weight**	2,050 lbs.**	930 kg**
Power Source	24v DC, 85Ah AGM Battery Pack	
Controls	Proportional Drive & Lift Controls	
Tires	9 in.	23 cm

*Metric equivalent of working height adds 2m to platform height. U.S. adds 6 ft. to platform height.

**Weight may vary with certain options or configurations.

Important - MEC scissor lifts must be on a hard level surface while elevated.
Warranty - MEC Aerial Work Platforms carry a one (1) year warranty on defective component parts and a five (5) year warranty on defective structural parts. This warranty applies to the original owner only. Consult your MEC dealer for warranty details.

Meets or exceeds the requirements of ANSI A92.20 and CSA B354.6.

Specifications subject to change without notice. Photos and diagrams in this brochure are for illustrative purposes only. Contact your MEC distributor for detailed instructions on the proper use and maintenance of this equipment.

Distributed by: